



EPSON Expression® 1680

Color Flatbed Scanner

The remarkable 1600 dpi, 48-bit scanner for graphic arts professionals.

A remarkable breakthrough in high quality imaging, the EPSON Expression 1680 is Epson's first 1600 x 3200 dpi flatbed scanner to feature, 48-bit color and a 3.6 Dmax. Optimized to consistently deliver enhanced colors, subtle highlights, and sharp shadow detail, this affordable scanner sets a new standard in image quality.

The EPSON Expression 1680 blazes through each scan with reliable performance and minimum noise. Our exclusive ColorTrue® II Imaging System and MatrixCCD™ technology combine custom optics, a Xenon lamp, Dynamic Range Control, and superior image processing for phenomenal results every time.

With the highest price/performance ratio in its category, this durable unit is perfect for your demanding workload as a graphics arts professional or photographer. Quickly and accurately, it delivers extraordinary results with virtually any original, from reflective media up to 8.5" x 11.7" and 35mm to 8" x 10" transparencies*. Its Dual-Focus Mechanism, in combination with its custom film holders, eliminates the "Newton Ring" problems often associated with less sophisticated scanners.

The scanner supports both USB and SCSI connectivity. With an optional high-speed FireWire® interface it's compatible with both the Power Mac™ G4 and the latest PCs. EPSON Scan Server software (PC) lets you network among Windows® and Macintosh® users. It's available in four configurations: Special Edition, Artist, Professional and Professional FireWire. The Professional and Professional FireWire models include powerful graphics software such as LaserSoft® SilverFast™ Ai 5 and a transparency unit.

Use the LaserSoft SilverFast scanner software to sharpen and descreen images, control color balance, tonal curves, highlights and shadows. Or, take advantage of its unattended batch scanning capabilities. Simply set all the settings at once and watch it scan all the images in one operation. An optional transparency unit and automatic document feeder are also available.

When teamed with an EPSON Stylus® Pro Series printer, the EPSON Expression 1680 is the perfect input/output solution.

* Optional transparency unit required.

Key Features

1600 x 3200 dpi optical resolution

Delivers remarkable resolution and extraordinary image quality

ColorTrue II Imaging and true 48-bit color depth

Produces smooth gradations and outstanding color reproduction; captures over 281 trillion colors (48-bit) and 65,536 shades of gray (16-bit)

Exceptional dynamic range (up to 3.6 Dmax for transparency scanning*)

Accurately scans each image; provides enhanced highlights and subtle shadow detail from transparencies; provides intelligent negative scanning for 35mm film strips

Dual-Focus Mechanism

Works with custom film holders to eliminate "Newton Rings" for clear, sharp results every time

High-speed scans and previews

Offers high speed image processing for increased productivity; creates full color preview in as little as 10 seconds; scans a 35mm slide at 1600 dpi in approximately 65 seconds; scans an 8.5" x 11" color photo at 300 dpi in approximately 23 seconds

USB and SCSI connectivity with optional FireWire interface

Provides trouble-free setup and installation for Windows and Macintosh systems

Premium software bundle**

LaserSoft SilverFast Ai 5 (professional scanning software)
 MonacoEZcolor™ (calibration software)
 Adobe® Photoshop® LE (image editing software)
 NewSoft™ Presto!® PageManager® (document management software)
 ScanSoft® TextBridge® Pro (OCR software)
 EPSON TWAIN Pro 2.0

** Included on the Artist, Professional, and Professional FireWire models. Special Edition model includes EPSON TWAIN Pro 2.0 software only.



EPSON Expression 1680

Shown here with optional transparency unit
 (included on Professional and Professional FireWire models)

EPSON Expression 1680

Scanner Type	Flatbed color image scanner
Scanning Method	Movement of reading mirror
Photoelectric Device	Color MatrixCCD Line Sensor
Maximum Read Area	8.5" x 11.7" (216mm x 297mm)
Light Source	Xenon gas cold cathode fluorescent lamp
CCD Resolution	1600 dpi
Hardware Resolution	1600 x 3200 dpi with Micro Step Drive™ technology
Maximum Resolution	13,600 x 18,720 dpi with interpolation
Effective Pixels	13,600 x 18,720 pixels (1600 dpi)
Image Data	
Color Depth	48 bits per pixel internal/external
Grayscale Depth	16 bits per pixel internal/external
Line Art	1 bit per pixel
Scaling (Zoom)	50% to 200% (1% step)
Optical Density	3.6 Dmax
Brightness	7 levels
Reading Sequence	One-pass scanning
Scanning Speed (1600 dpi, draft mode)	
Color	9.2 msec/line (approx.)
Grayscale/Monochrome	3.1 msec/line (approx.)

Operating Systems Supported

Macintosh	Macintosh OS 8.0 or later
PC	Windows 95, 98, 2000, Me or NT 4.0

Windows Minimum System Requirements

PC with Pentium® equivalent or higher processor
64MB RAM recommended

SCSI – Requires ASPI-compliant compatible Fast SCSI, Ultra or Ultra 2 SCSI PCI Card

USB – USB port equipped PC systems with Windows 98 (factory installed), Windows 2000 or Windows Me

IEEE 1394 FireWire – FireWire port equipped PC systems or PCI IEEE 1394 card (OHCI compliant) with Windows 2000 or Windows Me

Macintosh Minimum System Requirements

PowerPC™ processor or higher
64MB RAM recommended

SCSI – Requires Power Macintosh system with built-in SCSI port or a Mac-compatible PCI SCSI/SCSI-2 card with Mac OS 8.0 or later

USB – iMac, G3, G4 or USB port equipped Power Macintosh systems with Mac OS 8.5 or later

IEEE 1394 FireWire – iMac DV, Power Macintosh, G3, G4 and FireWire port equipped Power Macintosh systems with Mac OS 8.6 with FireWire Update 2.1 or later

Interface SCSI-2 and USB standard, IEEE 1394 FireWire optional

Configurations

Special Edition Model (MAC & PC) E1680-SE

EPSON Twain Pro Scanner Utilities
USB cable

Artist Model (MAC & PC) E1680-ART

EPSON TWAIN Pro Scanner Utilities
LaserSoft SilverFast Ai 5
MonacoEZcolor
Adobe Photoshop LE
ScanSoft TextBridge Pro OCR
NewSoft Presto! PageManager
USB cable

Configurations (cont.)

Professional Model (MAC & PC) E1680-PRO

Transparency Unit
EPSON TWAIN Pro Scanner Utilities
LaserSoft SilverFast Ai 5 (IT8 calibration kit included)
MonacoEZcolor
Adobe Photoshop LE
ScanSoft TextBridge Pro OCR
NewSoft Presto! PageManager
USB cable

Professional FireWire Model (MAC & PC) E1680-PROFWR

Transparency Unit
EPSON TWAIN Pro Scanner Utilities
LaserSoft SilverFast Ai 5 (IT8 calibration kit included)
MonacoEZcolor
Adobe Photoshop LE
ScanSoft TextBridge Pro OCR
NewSoft Presto! PageManager
FireWire cable

Reliability

MCBF 100,000 cycles

Environmental Conditions

Temperature Operating 41°F to 95°F (5°C to 35°C)
Humidity Operating 10% to 80% (no condensation)
Storage 10% to 85% (no condensation)

Power Requirements

Voltage AC 100V-120V, 220V-240V
Frequency 50-60Hz
Power consumption 60W operating w/o optional unit
75W operating w/optional unit
10W standby w/o optional unit

Physical Dimensions (scanner only)

Width 13.1" (332mm)
Depth 22.1" (562mm)
Height 5.2" (133mm)
Weight 18.7 lb (8.5 kg approx.)

Optional Accessories

Transparency Unit
Automatic Document Feeder
IEEE 1394 FireWire Scanner Interface Card

Product/Accessory Part Numbers

EPSON Expression 1680 Special Edition Scanner	E1680-SE
EPSON Expression 1680 Artist Scanner	E1680-ART
EPSON Expression 1680 Professional Scanner	E1680-PRO
EPSON Expression 1680 Professional FireWire Scanner	E1680-PROFWR
Transparency Unit	B813182
Automatic Document Feeder	B813162
IEEE 1394 FireWire Scanner Interface Card	B808342

Warranty

One year limited warranty in the U.S. and Canada
Optional extended service plans for Depot Repair and Express Exchange available

Support—The Epson ConnectionSM

Pre-sales support U.S. and Canada	800-463-7766
Automated Technical Support	800-922-8911
Internet Website	www.epson.com



YOU'VE GOT TO SEE IT IN **EPSON** COLOR.™

www.epson.com

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America
6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. Epson is a registered trademark and MatrixCCD is a trademark of Seiko Epson Corporation. EPSON Expression and ColorTrue are registered trademarks, Micro Step Drive is a trademark and Epson Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2001, Epson America, Inc. CPD-11690 1/01 50K LG Printed on Recycled Paper

